

## GULF COAST TMC, LLC

7670 Hwy 10 ● Ethel, LA 70730 (225) 683-6636 <sup>TEL</sup> ● (225) 683-6652 <sup>FAX</sup> sales@gulfcoasttmc.com ● www.gulfcoasttmc.com Ethel • Stonewall, LA

Houston • Odessa, TX

Where Service & Total Customer Satisfaction Make the Difference!

## PRAGMATICS...

Pragmatics Fire Arson Detector Model 626 Trooper 2 is a dual sensor accelerant detector designed for the arson investigator. Durable MOX sensors are paired and response balanced to eliminate nuisance water vapors and pyrolitic materials vapors which are common interferences to most commercially available single sensor instruments. With sensitivity down to 1 ppm, dual sensor Pragmatics arson instruments will find trace accelerant in 85% of the samples tested. For superior drip and pour location, the Trooper 2 is fitted with an LED meter for tracing rising and falling concentrations of gas, from 1 ppm through 1% gas (10,000ppm). Requiring no field calibration prior to starting a search and start and go technology, the 626 Trooper 2 arson detector is the choice of arson investigators, insurance claim representatives, and First Responders around the world.



626 Trooper II with Optional Tripod mount



## www.pragmaticsdetectors.com

## SPECIFICATIONS

CASE CONSTRUCTION	Brightstar lantern package, working	Response Time:	1 second
CASE CONSTRUCTION			
DIMENSIONS:	4.5" W x 8" L x 5" H lantern, probe 48" extended; 5 lbs.	Continuous Operation Time:	10 working hours
GAS DETECTED:	Heavy hydrocarbons such as Gasoline, Kerosene, Solvents	Power Source:	6v rechargeable lead acid battery
DETECTION PRINCIPLE:	Dual compensating semiconductor type	Controls:	Search/Zero, Tone/Off/Silent, Lantern On/Off, Super Search, Rate Logic
DETECTION RANGE:	1 ppm - 10,000 ppm	Standard Accessories:	Alkaline battery pack, lead acid rechargeable battery, 2 pc probe, AC and DC charging cords, rubber cup
Sampling Method:	Diffusion	<b>OPTIONAL ACCESSORIES:</b>	Pelican case, Tripod
DISPLAY SPECS:	LED meter 0-500 ppm and 0.1 - 1%gas	Applications:	Arson investigation
LED ALARMS:	1% Gas level (20% LEL), Multi Fault,	AVAILABLE AS:	Product
	Battery Status		
<b>O</b> PERATING <b>T</b> EMP:	20° - 120° F	SENSOR WARRANTY:	1 year (normal use)
<b>O</b> perating Humidity:	10 - 100% RH	INSTRUMENT WARRANTY:	1 year



LA facility. From simple RTU power to complex skid-mounted Measurement and Safety systems we have a solution to fit your needs. Leading Exploration, Production, and Transmission companies from around the United States rely on Gulf Coast's competitively priced, quick-turn manufacturing to satisfy their strict project requirements.



Odessa, TX (432) 653-4141 Stonewall, LA (318) 775-5679

> Butler, AL (225) 719-3077 Ethel, LA (225) 683-6636 Houston, TX (713) 325-6760